

Akuvox VP-R48G Android Video Operator Phone 7-inch touch screen, HD Voice quality and multifunction ip video phone which special designed for Operator, Security Guard...

- Multimedia video phone
- 7-inch touch screen
- Dual gigabit Ethernet ports
- Premium audio and video quality
- Support 3rd-party apps
- Android 5.1/SIP/RTSP/PoE

Overview

VP-R48G is a SIP-based, gigabit IP video phone for businesses of various scales featuring a 7" touch screen, a 2M CMOS camera sensor and Android Operating System. This multimedia terminal brings together diverse services for business settings, including high-definition audio and video calling, smooth internet surfing, daily information display and individualized business applications import from one's mobile phone.

Specifications

Physical Features

7" capacitive touch screen
 Display: TFT LCD, 1024*600 pixels, 16:9 aspect ratio
 LED light: 1 power light, 1 network light and 1 message light
 28 Keys, RK3066 chipset
 Flash memory: 8GB
 1GB DDR3 memory
 Camera: 2M-pixel CMOS sensor, free rotation
 PoE IEEE802.3af
 Power adapter: input-AC 100~240V, output-DC 12V/1A
 Power consumption: approx.14.4W
 Operating temperature: 32~ 104°F(0~ 40°C)
 Storage temperature: -4~ 158°F(-20 ~ 70°C)
 Operating humidity: 10% ~90% (non-condensing)
 Storage humidity: 10% ~ 90% (non-condensing)
 Weight: approx. 1.04kg
 Dimensions: 240x192x106mm
 Gift box size: 255x198x128mm

Interface Features

2xRJ45 10/100/1000M Ethernet ports
 Bluetooth
 Wireless access: 802.11b/g/n
 1xUSB flash drive 2.0, 1xRJ9 handset, 1x3.5mm headset jack
 1xHDMI video output port

Phone Features

Call Waiting, Call Transfer, Call Hold, Mute, Redial
 Speed Dial, DND, Direct IP call, 4-way conferencing

» Installation:

Indoor Outdoor

» Modulars:

Camera Touchscreen
 Keypad Button RFID

» Connections:

100Mbps x2 1Gbps x2 PoE
 Relays x3 Wifi Bluetooth

Camera Field of View (FoV):

90° FoV 120° FoV

SIP Features

SIP v2 (RFC3261)
 Line: 6 SIP accounts

Audio Features


Wideband codec: G.722
 Narrowband codec: PCMA, PCMU, G.723, G.729, OPUS, ILBC, AMR-NB and AMR-WB
 Echo cancellation
 Voice activity detection
 Comfort noise generator
 Full-duplex speakerphone
 DTMF mode: RFC2833, In-Band, SIP INFO and Auto

Video Features


Codec: H.263 and H.264
 Solution: QCIF, CIF, VGA, 4CIF and 720P
 Bitrate: 64kbps-2Mbps
 Adaptive bandwidth adjustment
 Image format: JPEG, GIF, PNG and BMP
 Other feature: PIP, full screen and local video ON/OFF control

Application Scenarios


Front Door communication and live view
 Apartment Communication
 Operator, Security Guard Door control
 Control remote entrances over the internet



Apartment's owner make a point-point video call to Operator / Security Guard



Security Guard make a point-point video call to owner or announce to all of owner via paging features



Security Guard able to make an emergency call